Salem Neighborhood Traffic Calming Program

Transportation Commission Meeting Feb 12, 2025



neighborwaysdesign

Outline

- Program Recap
- 2024 Neighborhood
 Traffic Calming Program
 Evaluation
- Feedback Period
- Next Steps + 2025 Program




2024 Traffic Calming Program Evaluation

2024 Pilot Installations

- Raymond Road
- Proctor Street
- Federal Street
- Mall Street


2024 Permanent Installation

- Chestnut Street
- Columbus Avenue




Raymond Road

Raymond Road











Raymond Road Data Collection

Raymond Road Traffic Volume Analysis









Raymond Road Traffic Volume Analysis











Raymond Road Traffic Volume Analysis









Rainbow Terrace Volume and Speed Analysis


Torrace


Seminary

Description



(No Calming During Raymond Pilot)





Raymond Road Evaluation Summary


From '23 to '24 pilot

- Raymond Road traffic decreased on average by 530 vehicles / day
- Rainbow Terrace traffic increased
 by 535 vehicles / day and speeds increased

Next Steps


- Collect data in spring on Rainbow Terrace before Raymond Rd reinstallation of Pilot speed humps
- Reevaluate design and consider calming on Rainbow Terrace





Proctor Street

Proctor Street










Proctor Neighborhood Data Collection

Proctor Street ADT Analysis







Average Daily Traffic (ADT)



Proctor Street Speed Analysis





Proctor Evaluation Summary


- Proctor Street speeds remained the same from 23' to '24:
 - Average Speed = 20mph
 - 85th % Speed = **23mph**
- In '24 Proctor and Witch Hill Rd traffic decreased by 255 and 343 vehicles / day respectively
- Next Steps
 - Reinstall Pilot
 - Coordinate with area projects and longer-term reconstruction






Federal Street

Federal St from North St to Boston St (0.55 mi)



Federal Street Pilot 3.0 – Iterative Design







Updated '24 Pilot 3.0:


- Extended humps further across Federal
- Adjusted locations and spacing on Federal between Beckford and North St after the Funeral home driveway
- Adjusted speed humps on side streets to midblock on, Monroe, Lynn, and Beckford
- Added speed hump on Flint St midblock between Essex and Federal

Federal St Data Collection




Federal Street ADT Analysis









Federal Street Speed Analysis: % over 20mph









Federal Street Speed Analysis: % over 25mph









Flint Street Analysis




June '23 - No Calming (During Federal Pilot 2.0) Nov '24 - Pilot Speed Humps 3.0





Federal Street Evaluation Summary


- '24 Pilot 3.0 average and 85th % speeds decrease by 1 – 2mph at all locations
 - Average Speed = 19mph
 - 85th % Speed = 22mph
- '24 ADT and speeds decreased
 - 60% decrease in speeding since 2021
 - 5% decrease in ADT since 2021
- Next Steps
 - Reinstall pilot speed humps



Mall Street

Mall Street







Mall Street Pilot









Mall Street Data Collection



Mall Street ADT Analysis








Mall Street Speed Analysis





Mall Street Evaluation Summary

Average Speed

Mall Street **16 mph**

Oliver Street **18mph**

85th % Speed

Mall Street **22mph**

Oliver Street **22 mph**


Oliver St speeds and volumes staying consistent

Reinstall Pilot humps

Chestnut Street & Columbus Avenue









Chestnut Street Summary

Chestnut Street ADT 2020 – 2024 by Calming Type




Chestnut Street Speeds 2020-2024 by Calming Type




Columbus Avenue Summary









Next Steps + 2025 Program


2025 Neighborhood Traffic Calming Program

2025 Permanent Installation

Point Zone – Harbor St, Dow Street,
 Palmer Street, and Leavitt Street

2025 Pilot Installations

- Proctor Street
- Federal Street
- Raymond Road
- Mall Street



Next Steps

Public Feedback Period

- www.publicinput.com/salemtrafficcalming
- Comment Period open until March 15, 2025

Early Spring

- Review Analysis and Feedback
- Planning and Design

Spring / Summer

Pilot and Permanent Installations





Q&A / Discussion

Project Contact

Christina HodgeAssistant Transportation Director

City of Salem chodge@salem.com


Public Comment
Period Open through
March 15, 2025
Scan or Visit



www.publicinput.com/salemtrafficcalming

More info visit:

https://traffic-calming-1-salemma.hub.arcgis.com/



Speed Hump Guidelines

Target location

- **Midblock on residential local streets,** especially those in the bicycle network and routes to school.
- **Not appropriate at intersections** (raised crossings and raised intersections may be installed at intersections based on engineering judgment)
- Not appropriate on short dead-end streets, streets with hospitals, designated emergency response routes, snow emergency routes, evacuation routes, and major bus routes.
- Maximum roadway grade = 8%
- Minimum horizontal curve radii = 300ft
- Target speed = 20 to 25mph
- **Target spacing = 280' for 20mph**, with a minimum of 200' to 400' maximum spacing based on-site constraints and engineering judgment.

Speed Hump Guidelines

Offsets

- 100' minimum to 200' maximum from intersections.
- 10' minimum from driveways and fire hydrants.
- 1' minimum to 2' maximum from curbs or edge of pavement.

Signs and Markings

- Provide a minimum of one speed hump warning sign at every permanent asphalt speed hump to alert
 plow drivers during winter. Temporary rubber speed humps used for pilots are removed in winter; signs may or
 may not be installed based on engineering judgment.
- Speed hump pavement markings following the latest standards in the MUTCD may be used based on engineering judgment.

Additional location considerations

- Consider installing where there are existing vertical fixed objects on at least one side of the road (e.g., trees, light poles, utility poles, etc.) to reduce drivers from swerving around humps and mounting sidewalks.
- Ideal at property lines and light poles where feasible.